

MFWD TRACTORS

Models 335 and 360



GROUNDBREAKING POWER

VERSATILE MFWD TRACTORS ARE INDUSTRY LEADING, FULL-FEATURED TRACTORS WITH OVER 20 YEARS OF FIELD PROVEN PERFORMANCE. Introducing the Versatile MFWD 335 and 360 tractors powered by the Cummins QSL9 engine that delivers a combination of power, economy and performance. The Cummins engine is matched to a smooth shifting powershift transmission that has 16 forward and 9 reverse speeds with operator programmable features designed to match your work requirements. Finger tip electro-hydraulics with the optional Hi-Flow hydraulics package deliver 72 GPM (273 L/min) to meet the demands of modern implements. The optional suspended axle increases stability and traction providing increased operator comfort, decreases stress on the tractor and improved power to the ground performance by eliminating power hop and increasing tractive effort providing what you need - **GROUNDBREAKING POWER.**



Featuring the largest cab
in the industry

- » **CUMMINS QSL9 ENGINE**
- » **TIER 4F EMISSIONS**
- » **16 X 9 POWERSHIFT TRANSMISSION**
- » **SUSPENDED AXLE**
- » **2-YEAR / 2000-HOUR WARRANTY**
- » **DESIGNED FOR EASY SERVICEABILITY. ROUTINE SERVICE CAN EXTEND THE LIFE OF YOUR TRACTOR, MINIMIZE DOWNTIME AND LOWER OPERATING COSTS.**

SEE YOUR VERSATILE DEALER FOR ALL FEATURES AND OPTIONS.

WWW.VERSATILE-AG.COM

	335	360
ENGINE		
Engine type	Cummins QSL9 T4F	Cummins QSL9 T4F
Aspiration	Turbocharged & air-to-air aftercooled	Turbocharged & air-to-air aftercooled
Displacement	9-liter	9-liter
Horsepower	335 hp (250 kW) @ 2100 RPM	360 hp (268 kW) @ 2100 RPM
Power bulge	10% @ 1900 RPM	11% @ 1900 RPM
Peak horsepower	370 hp (276 kW)	400 hp (298 kW)
Torque rise	35% @ 1500 RPM	33% @ 1500 RPM
Peak torque	1130 lb-ft (1532 N•m)	1199 lb-ft (1626 N•m)
FUEL SYSTEM		
Capacity	165 U.S. gal (625 L)	165 U.S. gal (625 L)
DEF tank	9 U.S. gal (34 L)	9 U.S. gal (34 L)
Filter	Engine mounted w/water separator	Engine mounted w/water separator
TRANSMISSION		
Powershift transmission	16 forward speeds, 9 reverse	16 forward speeds, 9 reverse
Maximum speed	25 mph (40 kph)	25 mph (40 kph)
AXLES		
Front axle w/limited slip	Standard	Standard
Suspended axle w/differential lock	Optional	Optional
Front axle track setting	60 to 88 in (1524 to 2235 mm)	60 to 88 in (1524 to 2235 mm)
Rear bar axle diameter	4.7 in (120 mm)	4.7 in (120 mm)
Rear axle track setting (w/120" axle)	60 to 120 in (1524 to 3048 mm)	60 to 120 in (1524 to 3048 mm)
HYDRAULICS		
Hydraulic type	Closed Center Load Sensing System	Closed Center Load Sensing System
Standard flow	55 GPM (208 L/min)	55 GPM (208 L/min)
Hi-Flow hydraulic system	72 GPM (273 L/min)	72 GPM (273 L/min)
Hydraulic remotes - Standard flow	4 standard	4 standard
Hydraulic remotes - Hi-Flow	6 standard	6 standard
Maximum system pressure	2900 PSI (197 bar)	2900 PSI (197 bar)
ELECTRICAL SYSTEM		
Alternator	12V - 200 amps	12V - 200 amps
Batteries	2-12V, 950 CCA ea.	2-12V, 950 CCA ea.
Standard lights	Halogen - 2 headlights, 9 worklights, 2 front roof mounted	Halogen - 2 headlights, 9 worklights, 2 front roof mounted
HID lighting / Power mirrors	Optional / Optional	Optional / Optional
DRAWBAR / 3-POINT HITCH / PTO		
3-point hitch	Category IVN	Category IVN
Standard (SAE) lift capacity	17,260 lb (7829 kg)	17,260 lb (7829 kg)
PTO, 1000 RPM	Standard	Standard
CAB		
Volume	149 cu. ft. (4.22 cu. m)	149 cu. ft. (4.22 cu. m)
Glass	74 sq. ft. (6.88 sq. m)	74 sq. ft. (6.88 sq. m)
WEIGHTS & DIMENSIONS		
Weight, unballasted	23,945 lb (10,861 kg)	23,945 lb (10,861 kg)
Max. operating weight	35,400 lb (16,057 kg)	35,400 lb (16,057 kg)
Wheelbase	128.95 in (3275 mm)	128.95 in (3275 mm)
Turning radius*	18.3 ft @ 30° row spacing (5.6 m @ 762 mm)	18.3 ft @ 30° row spacing (5.6 m @ 762 mm)
Overall length, w/front weights	251 in (6375 mm)	251 in (6375 mm)
Height, top of cab†	131.5 in (3335 mm)	131.5 in (3335 mm)

* w/380/80R38 singles

† w/RCL 48 tires



Now you can purchase or lease your equipment with competitive rates through Versatile Finance. Versatile has partnered with one of the foremost leaders in agricultural financial services to provide attractive interest rates and fast acceptance to get you the equipment you need when you need it. Ask your dealer about the credit options available with Versatile Finance.



©2016 Buhler Versatile Inc. All Rights Reserved » info@versatile-ag.com » www.versatile-ag.com
Ref: 0820163000 LM

Illustrations, photographs and specifications in this brochure are based on the latest information at the time of publication. Design and specification of equipment is subject to change without notice; please contact your local dealer for product information and availability. Products produced by other manufacturers featured in photography are not endorsed by Buhler Versatile Inc. and are intended for image reference only.